

# Onsite Elevated Sealed Silos



## FEATURES & INCLUSIONS

- Sight glasses x 2 in top and bottom barrels to indicate level in silo
- Safety ladders and cages that comply with Australian Standard AS1657
- Slide ladder that lock into place above ground to prevent accessibility to children and visitors
- Ground Opening Lid
- Models can be custom designed to client requirements
- Manhole in base
- Installation
- Silos sealed gas tight complying with Australian standard AS2628, including pressure relief valve



**National Grain Solutions – A subsidiary of HE Silos Gunnedah Providing premium onsite grain storage products for the Australian agricultural industry.**

### AUSTRALIAN MADE & FAMILY OWNED

A family business with a wealth of knowledge and experience, we can confidently assist you in your new purchase. Our silos are engineered to last.

### QUALITY

Our skilled staff are equipped to produce top-tier products. We maintain our commitment to quality through a rigorous assurance program, ensuring that each product meets our high standards. All our products are crafted from premium galvanized steel.

### WARRANTY

National Grain Solutions offers necessary repairs or replacements under warranty. We differ from others with our follow up service to ensure your product is operating to your needs. Every product is backed by a 5-year warranty to safeguard consumers.

## SILO EXCLUSIONS

- Concrete silo foundation
- Crane hire to load silo roof & barrels from truck to site & onto silo base
- Freight



Model	Tonnes	Cubic meters	Height	Diameter	Auger length	Cone Degree	Cone to Ground
140T	140	171m <sup>3</sup>	9.55m	5.6m	(60') 18.3m	35	600mm
190T	190	240m <sup>3</sup>	10.4m	6.55m	(65') 20.0m	35	600mm
260T	260	320m <sup>3</sup>	10.35m	7.5m	(65') 20.0m	35	700mm
305T	305	377m <sup>3</sup>	11.5m	7.5m	(73') 22.0m	35	700mm
500T	500	630m <sup>3</sup>	13.5m	9.4m	(75') 23.0m	35	700mm

1. Capacity is approximate and based on wheat typical consolidated with a 5% compaction in silo.
2. Max. Load based on engineering design for wheat at 810kg/m<sup>3</sup>.
3. Auger lengths are indicative only and are based on 35° angle. As differing auger brands elevate to different angles, always check individual auger height.
4. Covered by a 5 year warranty



30 Borthistle Road, Gunnedah NSW 2380

**Phone:** 1300 764 700

**Email:** [sales@ngssilos.com.au](mailto:sales@ngssilos.com.au)

**Website:** [www.ngssilos.com.au](http://www.ngssilos.com.au)

Connect with us

